

Coil Copper Tube

Keyword: soft coil, coil pipe, coil tube, pancake copper pipe, copper pipe, copper tube

Application: Widely used for air-conditioning and refrigeration field service, heat exchange use, connecting tubes, distribution, fire protection, solar, natural gas, liquefied petroleum gas, vent piping.

Alloy: C12200 (UNS), SF-Cu 2.0090 (DIN), Cu-DHP CW024A (EN)

Temper: Soft drawn

Package: Ends capped, in shrinking -wrapped bag, then into cardboard box

Standard: ASTM EN JIS KS BS DIN

Outside Diameter		Thickness		Nominal Weight (Kgs)		Package
inch	mm	inch	mm	15m	50'	Q'ty/Carton
1/8"	3.18	0.030	0.76	0.78	0.79	15
3/16"	4.76	0.030	0.76	1.28	1.31	15
1/4"	6.35	0.030	0.76	1.79	1.82	10
5/16"	7.94	0.032	0.81	2.44	2.48	10
3/8"	9.52	0.032	0.81	2.98	3.03	10
1/2"	12.7	0.032	0.81	3.59	3.65	5
5/8"	15.87	0.035	0.89	4.85	4.93	5
3/4"	19.05	0.035	0.89	6.25	6.35	4
7/8"	22.23	0.045	1.14	10.16	10.32	4

Note: other size can be made as per customer's requirement
the minimum thickness is 0.45mm