

Straight Copper Tube

Keyword: hard Straight copper tube, hard copper tube, hard tube, copper pipe, copper tube

Application: Widely used for air-conditioning and refrigeration field service, heat exchange use, connecting tubes, distribution, fire protection, solar, natural gas, liquefied petroleum gas, vent piping.

Alloy: C12200 (UNS), SF-Cu 2.0090 (DIN), Cu-DHP CW024A (EN)

Temper: Hard drawn

Package: Ends capped, into polybags or in wooden case(with additional charges)

Standard: ASTM EN JIS KS BS DIN

Outside Diameter		Wall Thickness		Nominal Weight (kgs)		Package
inch	mm	inch	mm	5 m	20'	Q'ty/Carton
3/8"	9.525	0.030	0.762	0.94	0.953	20
1/2"	12.700	0.035	0.889	1.48	1.499	20
5/8"	15.875	0.040	1.016	2.12	2.155	15
3/4"	19.050	0.042	1.067	2.70	2.739	12
7/8"	22.225	0.045	1.143	3.39	3.440	12
1-1/8"	28.575	0.050	1.270	4.87	4.950	10
1-3/8"	34.925	0.055	1.397	6.58	6.686	5
1-5/8"	41.275	0.060	1.524	8.51	8.648	5
2-1/8"	53.975	0.070	1.778	13.04	13.248	3
2-5/8"	66.675	0.080	2.032	18.46	18.751	2
3-1/8"	79.375	0.090	2.286	24.76	25.156	1
3-5/8"	92.075	0.100	2.540	31.95	32.464	1
4-1/8"	104.775	0.110	2.794	40.03	40.674	1

Note: other size can be made as per customer's requirement
the minimum thickness is 0.45mm

