

## MIDAIR R410A-WALL MOUNTED ON/OFF

Model NO.	Indoor Unit Outdoor Unit	MSAFA-09CRN1 MSAFA-09CRN1	MSAFB-12CRN1 MSAFB-12CRN1	MSAFB-18CRN1 MSAFB-18CRN1	MSAFD-24CRN1 MSAFD-24CRN1	MSABF-30CRN1 MSABF-30CRN1		
<b>Performance</b>								
Power Supply	V~, Hz, Ph	220-240V,50Hz-,1ph	220-240V,50Hz-,1ph	220-240V,50Hz-,1ph	220-240V,50Hz-,1ph	220-240V,50Hz-,1ph		
Cooling Capacity	Btu/h	9000	12000	18000	24000	27000		
	kw	2.6/2.8	3.5/3.5	5.28/5.56	7.03/7.32	7.91/8.79		
EER	W/W	3.21	3.21	3.21	3.01	3.61		
Energy Rate		A	A	B	B	A		
Air Flow Volume	Indoor	H/M/L M3/h	510/380/338	568/440/352	820/665/543	1000/796/640	1089/931/854	
	Outdoor	H/M/L dB (A)	40/33/26	41/36/31	44/38/33	48/40/34	50/46/44	
Noise Level	Indoor	H/M/L dB (A)	40/33/26	41/36/31	44/38/33	48/40/34	50/46/44	
	Outdoor	dB (A)	55.5	56	59	60	60	
<b>Dimension &amp; Weight &amp; Piping Size</b>								
Net Dimension	Indoor	WxDxH	mm	715x194x285	805x194x285	958x302x223	1038x325x235	1080x226x335
	Outdoor	WxDxH	mm	700x270x550	770x300x555	770x300x555	845x363x702	946x420x810
Packing Dimension	Indoor	WxDxH	mm	780X270X360	870X270X360	1035X380X295	1120X310X405	1155X415X315
	Outdoor	WxDxH	mm	815X325X615	900X345X585	900X348X615	965X395X755	1090X500X875
Net / Gross Weight	Indoor	KG		7.2 / 9.4	7.7 / 1.0	10.2 / 13.3	12.7 / 16.4	15.2 / 17.2
	Outdoor	KG		26.4 / 28.6	30 / 32.3	35.8 / 38.2	49 / 52	55 / 58

## MIDAIR SPECIFICATION - R410A-WALL MOUNTED DC INVERTER COOLING ONLY

Model NO.	Indoor Unit Outdoor Unit	MSAFB-12CRDN1 MSAFB-12CRDN1	MSAFC-18CRDN1 MSAFC-18CRDN1	MSAFD-24CRDN1 MSAFD-24CRDN1		
<b>Performance</b>						
Power Supply	V~, Hz, Ph	220-240V-50Hz-,1ph	220-240V-50Hz-,1ph	220-240V-50Hz-,1ph		
Cooling Capacity	Btu/h	12000/12000	18000/18000	24000/24000		
	kw	3.5/3.5	5.3/5.3	6.45/6.89		
EER/COP	W/W	3.01/3.21	3.21/3.41	3.21/3.41		
Air Flow Volume	Indoor	H/M/L M3/h	568/440/352	820/665/543	1000/796/640	
Noise Level	Indoor	H/M/L dB (A)	41/36/31	43/38/33	47/40/34	
	Outdoor	dB (A)	56	56	60	
<b>Dimension &amp; Weight</b>						
Net Dimension	Indoor	WxDxH	mm	805x194x285	957x213x302	1040x220x327
	Outdoor	WxDxH	mm	770x300x555	770x300x555	845x363x702
Packing Dimension	Indoor	WxDxH	mm	870X270X360	1035X295X380	1120X310X405
	Outdoor	WxDxH	mm	900X345X585	900X345X585	965X395X755
Net / Gross Weight	Indoor	KG		7.7 / 1.0	10.2 / 13.3	12.7 / 16.4
	Outdoor	KG		26 / 28.4	30.5 / 32.5	45.6 / 48.8

## MIDAIR - FOREST SPLIT SPECIFICATION - R410A-WALL MOUNTED DC INVERTER HEATING/COOLING

Model NO.	Indoor Unit Outdoor Unit	MSAFB-12HRDN1 MSAFB-12HRDN1	MSAFC-18HRDN1 MSAFC-18HRDN1	MSAFD-24HRDN1 MSAFD-24HRDN1		
<b>Performance</b>						
Power Supply	V~, Hz, Ph	220-240V-50Hz-,1ph	220-240V-50Hz-,1ph	220-240V-50Hz-,1ph		
Cooling Capacity	Btu/h	11500/12500	18000/18500	24000/25000		
	kw	3.5/3.5	5.25/5.56	6.45/6.89		
SEER	W/W	6.2	6.2	6.2		
Air Flow Volume	Indoor	H/M/L M3/h	568/440/352	820/665/543	1000/796/640	
Noise Level	Indoor	H/M/L dB (A)	41/36/31	44/38/33	48/40/34	
	Outdoor	dB (A)	56	56	60	
<b>Dimension &amp; Weight &amp; Piping Size</b>						
Net Dimension	Indoor	WxDxH	mm	805x194x285	957x213x302	1040x220x327
	Outdoor	WxDxH	mm	770x300x555	770x300x555	845x363x702
Packing Dimension	Indoor	WxDxH	mm	870X270X360	1035X295X380	1120X310X405
	Outdoor	WxDxH	mm	900X345X585	900X345X585	965X395X755
Net / Gross Weight	Indoor	KG		7.7 / 1.0	10.2 / 13.3	12.7 / 16.4
	Outdoor	KG		26 / 28.4	30.5 / 32.5	45.6 / 48.8



**LMY MARKETING LTD.**  
20 Louis Alfred Célestin St - Port Louis - Mauritius  
Tel: (230) 211 0888 - 210 3430 - Email: sales@lmy.mu

